


Clark Hot 17

Hot water self-contained unit with integrated electric generator



Standard equipment

- 6.601.0001 Gun PRO S'10 3/8" M with quick connection



- 6.602.0043 Lance 900 mm with quick connection.



- 3.103.0056 Nozzle type 075



- 4.618.0143 High pressure hose 10 m



- Available on request sound proofing steel model: CLARK HOT 17 SILENCED



cod. 8.601.0160

Clark Hot 17

- Hot water self-contained unit with integrated electric generator and max 1,5 kW fixed socket. • 17 HP Lombardini 2 cylinder water cooled diesel engine with electric start, complete with panel with engine function led and automatic power cut-off. • Three ceramic pistons, brass linear pump head with separated by-pass valve. • Suction and delivery S/S valves. • Max water inlet temperature 40° C. • Belt driven pump (1450 RPM). • Automatic engine RPM regulator • Manual power control • Loose by-pass outlet • Pressure regulator.
- Glycerine pressure gauge. • Flow rate regulator • Unique diesel tank for engine and burner • Tough steel main frame • Battery included

Technical data:	Clark Hot 17
Code	8.601.0058
Operat. pressure bar	30÷200
l/h	1320
Max water temperature	30÷140° C
RPM pump	1600
engine type	Lombardini diesel
Motor HP	17