

## Sundek 5 XP



### Standard equipment

- 3.700.0030 Gun M22 - 3/8" (mod 1211 XP-1511 XP).



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045
- 3.103.0049 Nozzle type 040



- 4.618.0143 High pressure hose 10 m



- Power cable 5 m

## Sundek5

- Three ceramic coated pistons, brass axial pump head with built-in bypass valve. • Vertical burner with high thermal efficiency steel coil.
  - Suction and delivery S/S valves. • Safety valve.
- Temperature regulation gauge. • Glycerine pressure gauge. • Automatic Stop System late shut down protection 24V. • Adjustable detergent delivery with built-in tank for indirect suction. • Two ways fuel pump
  - Low fuel lamp. • Ergonomic handles and impact resistant covers.
    - Accessory holder. • Power cable (m 5).

### Optional:

- Hose-reel with brake.(cod. 6.608.0019) • Header tank
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) cod. 3.697.0044

Technical data:	Sundek5 30	Sundek5 40
Code	8.620.0606	8.620.0607
Operat. pressure bar	30 ÷ 120	30 ÷ 150
l/h	330 ÷ 660	330 ÷ 660
Temp. max	140°C	140°C
Power ass. kW	3,2	4
RPM	2800	2800
Voltage	230 V~50 Hz	400 V~50 Hz