

Walk-behind floor scrubber driers

Standard equipment



With maintenance free Battery included

Technical data::	A1 36 E	A1 36 B
Code	8.518.0008	8.518.0007
power supply	230 V~50 Hz	1 x 12 V
scrubbing width	360 mm	360 mm
squeegee width	460 mm	460 mm
max working capacity	1260 m²/h	1260 m²/h
detergent tank capacity	11 l2.9 gal	11 2.9 gal
recovery tank capacity	12/13 l.	12/13 l.
traction	mechanical	mechanical
brush motor	370 W	250 W
vacuum motor	400 W	180 W



• 5.511.1346 PPL brush Ø 360 mm - 15"



4.508.1040
Front squeegee blade
L.537 mm - Th. 2.5 mm
4.508.1041
Rear squeegee blade
L.590 mm - Th. 3 mm



• 0.108.0061 On-board Battery charger 12V 8A only for model code: 8.518.0007



• 0.107.0061 Maintenance free battery 12V 55Ah BT DC 4.2 only for model code: 8.518.0007



Watch the video on youtube: www.youtube.com/fasavideo

A1 36

Suitable to work in high congested areas like small shops, offices, kitchens, schools, hospitals, bars, gyms, restaurants
Adjustable flow (automatic start-stop with solenoid valve) of the detergent solution depending on type of surface
Brush with quick release
Removable recovery tank
Available in battery version (36B) with integrated battery charger with data memory and for any type of batteries
Battery included
Squeegee lifting lever
Compact reclining handle with control switches
Easy access and simple service of the components.

PROFESSIONAL LINE



Walk-behind floor scrubber driers

Optional accessories:

• 0.107.0065

Battery AGM

12V 60Ah C5





• 0.108.0051 Booster battery charger



• 4.508.1058 Polyurethane front blade L.537 TH. 2,5 • 4.508.1059 Polyurethane rear blade L.590 TH. 3





• 5.511.1129 EWU pad driver Ø 360mm-14"

Abrasive pad Ø 381 mm-15"

Abrasive pad Ø 381 mm-15"

Abrasive pad Ø 381 mm-15"

Extension electric cord 15 m

• 6.508.0143

- beige (5 pcs.)

• 6.508.0144

- green (5 pcs.)

• 6.508.0141

- black (5 pcs.)

• 4.512.0068

with Schuko plug



The unit can be supplied mains (15 m cable available) or battery powered. Reclining handle: fit on any operator's height and allowing the perfect cleaning also on 90° corners. Shock-absorbing covers , simple cleaning of the recovery tank, non





marking wheels . Easy access to mechanical parts (easy maintenance of each component), removable recovery tank without tools.

> User friendly analogic control panel. Control lever for brush operation and detergent water outflow. General ON/OFF switch, brush and vacuum motor switch, solenoid valve operation switch.





Parabolic squeegee, easy rubber blades replacement. The floating brush plate and squeegee grant the right cleaning pressure on any type of floor.

PROFESSIONAL LINE