

Walk-behind floor scrubber driers

A12



Standard equipment

6

A12 66T

• 2 x 5.511.1105 PPL brush Ø 330 mm - 13"



A12 75T

• 2 x 5.511.1168 PPL brush Ø 360 mm - 14"



- 4.508.0646 Front squeegee blade L.925 mm Shore 40 Th. 3 mm
- 4.508.0605 Rear squeegee blade L.1015 mm Shore 30 Th. 4 mm

Technical data:	A12 66T	A12 75T
Code	8.517.0104	8.517.0106
power supply	24 V DC	24 V DC
scrubbing width	660 mm	750 mm
squeegee width	900 mm	900 mm
max working capacity	3762 m²/h	4275 m2/h
detergent tank capacity	88	88 I
recovery tank capacity	91/95	91/95
traction	300W/automatic	300W/automatic
vacuum motor	1733 mmH ² O/550W	1733 mmH ² O/550W

A12

Capable to work for the maintenance and deep cleaning of large areas (up to 2.600 m²)
User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch • Large handle with traction driving lever for forward and backward directions • Self levelling brush plate • Cover removable without tools • Quick vacuum motor and filter inspection, without tools • Detergent solution filter • Detergent solution tank provided with large opening protected by quick locking cap.

Walk-behind floor scrubber driers



Easy access to battery and vacuum motor compartment, without using tools. Large capacity shock and acid proof polyethilene tanks (88 l) avoid frequent refilling and idle time. 4 x 6V

granting continuous working time up to 4-5 hours. Adjustable speed ensures high precision in cleaning congested areas with obstacles. Intuitive controls reduce operator's training time. Safety thermal breakers prevent motor problems





in case of overheating or operator's misuse. Heavy duty V-shaped squeegee ensures perfect drying of every type of floor, even with large joints. Nonmarking wheels avoid marks after the drying. Completely adjustable to fit any surface.

Strong mechanical control levers for heavy duty use. Large size drain hose for a fast emptying and a better cleaning of the recovery tank. Quick fitting battery charger plug.





Optional accessories:



• 4 x 0.107.0004 Tubular battery Pb-acid 6V 180Ah C5



4 x 0.107.0072
GEL Battery 6 MFP 180
6V 180Ah C5



• 0.108.0002 Battery Charger 24V 25A 220-240/50-60

• 5.511.1495 On-board Battery charger kit - 24V - 25A



• 4.508.0901 Polyurethane front blade L.925 TH.3 Sh.40

• 4.508.0900 Polyurethane rear blade L.1015 TH.4 Sh.40



• 5.511.1106 Tynex brush Ø 330 mm-13" • 5.511.1246 Tynex brush Ø 360 mm-14"

• 5.511.1255 PPL 0,03 brush Ø 330 mm-13″ • 5.511.1169 PPL 0,03 brush Ø 360 mm-14″

• 5.511.1202 PES brush Ø 330 mm-13″ • 5.511.1203 PES brush Ø 360 mm - 14″



• 5.511.1107 EWU pad driver Ø 330 mm-13"

• 5.511.1129 EWU pad driver Ø 360 mm-14"



(5 pcs package)

• 6.508.0030 - Ø 340 mm-13"- beige

• 6.508.0037 - Ø 340 mm-13"- green

• 6.508.0044 - Ø 340 mm-13"- black

• 6.508.0143 - Ø 380 mm-15"- beige

• 6.508.0144 - Ø 380 mm-15"- green

• 6.508.0141 - Ø 380 mm-15"- black