

A5 EVO



Watch the video on youtube:
www.youtube.com/fasavideo

| Technical data: | A5 EVO 50 E | A5 EVO 50 | A5 EVO 50 T |
|-------------------------|------------------------|------------------------|------------------------|
| Code | 8.527.0005 | 8.527.0006 | 8.527.0008 |
| power supply | 230 V - 50 Hz | 24V | 24V |
| scrubbing width | 500 mm | 500 mm | 500 mm |
| squeegee width | 800 mm | 800 mm | 800 mm |
| max working capacity | 2000 m ² /h | 2000 m ² /h | 2000 m ² /h |
| detergent tank capacity | 44 l | 44 l | 44 l |
| recovery tank capacity | 50/60 l | 50/60 l | 50/60 l |
| traction | mechanical | mechanical | automatic |
| vacuum motor | 1000W | 480W | 480W |

Standard equipment



- 5.511.1097
PPL brush Ø 483 mm - 19"



- 4.508.X468
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- 0.108.0042
On-board Battery charger CBHD1 24V 10A
only for model code:
8.527.0007 - 8.527.0008
8.527.0013



- 0.107.0054
Maintenance free battery
12V 75Ah BT DC 5.5
only for model code:
8.527.0013

Other available versions:

- 8.527.0013 - A5 Evo 50B with batteries and battery charger
- 8.527.0007- A5 Evo 50B with battery charger

A5 EVO

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve (battery model only)
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

Walk-behind floor scrubber driers



Powerful gearmotor; metal brush plate with integrated plastic splash guard/ bumper.

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.



Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the

event of accidental impact. Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning solution.



Optional accessories:



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5




- 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4



- 5.511.1098 Tynex brush Ø 483 mm-19"
- 5.511.1128 PPL 0,03 brush Ø 483 mm-19"
- 5.511.1206 PES brush Ø 483 mm - 19"



- 5.511.1099 EWU pad driver Ø 483 mm-19"



- 6.508.0034 Abrasive pad Ø 483 mm-19" - beige (5 pcs.)
- 6.508.0041 Abrasive pad Ø 483 mm-19" - green (5 pcs.)
- 6.508.0048 Abrasive pad Ø 483 mm-19" - black (5 pcs.)



- 4.512.0068 Extension electric cord 15 m with Schuko plug